DMStechnologies

RITAR LITHIUM BATTERIES

TECHNICAL FEATURES

SAFETY

- LiFePO4 cells, high consistency, long cycle life and much more safety.
- UN38.3, CE certification for system.
- Prismatic LiFePO4 cells, high consistency, long cycle life and much more safety.
- The cycle life over 3000 times @80% DOD.

DESIGN

- ABS container, replace VRLA battery perfectly.
- Fast charge performance.
- -20~+55° C wide temperature range.
- Maintenance free.

BATTERY MANAGEMENT SYSTEM

- Integrated hardware BMS inside.
- Independent protection for charge and discharge.
- Over voltage, low voltage, over temperature and short circuit protection.
- Bluetooth communication, APP for Android and iPhone. (Only on 100Ah model)











T: +44 (0) 1794 525400

E: sales@dmstech.co.uk

SPECIFICATIONS

	12.8 V 6 AH	12.8V 12 Ah	12.8V 20Ah	12.8V 50Ah	12.8V 100Ah
RATED VOLTAGE (V)	12.8				
RATED CAPACITY (AH)	6	12	20	50	100
LENGTH (MM)	151	151	181	198	330
WIDTH (MM)	65	65	77	166	172
HEIGHT (MM)	93.5	93.5	167	169	214
WEIGHT (KG)	0.82	1.21	2.9	6.5	13.4
TERMINAL	F2	F2	F13-BP (Ø12, M5)	IF11 (Ø14, M6)	F12 (Ø17.5, M8)
COMMENTS	N/A				Bluetooth